



十速

TK8811CS

DATA SHEET

Rev 0.90

tenx reserves the right to change or discontinue the manual and online documentation to this product herein to improve reliability, function or design without further notice. **tenx** does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others. **tenx** products are not designed, intended, or authorized for use in life support appliances, devices, or systems. If Buyer purchases or uses **tenx** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **tenx** and its officers, employees, subsidiaries, affiliates and distributors harmless against all claims, cost, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use even if such claim alleges that **tenx** was negligent regarding the design or manufacture of the part.

AMENDMENT HISTORY

Version	Date	Description
V0.90	Jun, 2022	New release.


CONTENTS


AMENDMENT HISTORY	2
FEATURES	4
APPLICATION CIRCUIT	4
PIN ASSIGNMENT	5
PIN DESCRIPTION	5
FUNCTIONAL DESCRIPTION	6
1. Output Pin Mode Selection	6
1.1 Direct output mode.....	6
1.2 Toggle output mode	6
2. Touch Sensitivity Adjustment.....	7
3. Key Press Timeout Reset	7
4. Normal mode and Low Power mode.....	7
ELECTRICAL CHARACTERISTICS	8
Absolute Maximum Ratings	8
DC Characteristics (TA=25°C)	8
PACKAGE INFORMATION	9
Ordering Information	9
Package Information	10

FEATURES

1. One Key Touch Detector
2. Operation Voltage: 2.1V~5.5V
3. Operation Current: Normal mode =3.7uA / Low Power mode=2.7uA @V_{DD}=3V
4. Enter Low Power mode after no activity for 10 second
5. Response Time: Normal mode < 60mS; Low Power mode < 120mS
6. Sensitivity adjusted by TK pin capacitor (0pF~30pF)
7. Selectable output level: Active High or Active Low
8. Selectable output mode: Toggle or Direct mode
9. Key press timeout reset: 8 second
10. LVR=2.0V
11. SOT23-6 / DFN-6 package

APPLICATION CIRCUIT



PIN ASSIGNMENT

PIN DESCRIPTION

Name	In/Out	Pin Description
OUT	O	Touch Key output
TK	I	Touch Key input
TGL	I	OUT pin mode selection connect to VDD: OUT is Toggle mode output connect to VSS: OUT is Direct mode output
AHB	I	OUT output level selection connect to VDD: OUT is CMOS active low output connect to VSS: OUT is CMOS active high output
VDD, VSS	P	Power input pin and ground

FUNCTIONAL DESCRIPTION

1. Output Pin Mode Selection


The OUT pin mode is defined by TGL, AHB

TGL	OUT output mode
VDD	Toggle mode
VSS	Direct mode

AHB	OUT output level
VDD	CMOS active Low
VSS	CMOS active High


1.1 Direct output mode

This mode needs to connect TGL to VSS. The Direct mode waveform is as shown below.



1.2 Toggle output mode

This mode needs to connect TGL to VDD. The Toggle mode waveform is as shown below.



2. Touch Sensitivity Adjustment

The sensitivity of touch key can be adjusted by the capacitance of TK pin. The adjustment range is from 0 pF to 30 pF. Smaller capacitance can make higher sensitivity.

3. Key Press Timeout Reset

Long press on the touch key will produce a timeout reset. The maximum time is 8 seconds.

4. Normal mode and Low Power mode

The chip starts at Normal mode after reset. If no event occurred for 10 second, it switches to Low Power mode. It switches to Normal mode after sampling TK pin's capacitance variation event.


ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings

Parameter	Rating	Unit
Supply voltage	$V_{SS}-0.3 \sim V_{SS}+5.5$	V
Input voltage	$V_{SS}-0.3 \sim V_{DD}+0.3$	
Operating temperature	-20 ~ +70	°C
Storage temperature	-65 ~ +150	

DC Characteristics (TA=25°C)

Parameter	Sym	Conditions		Min	Typ	Max	Unit
Input High Voltage	V_{IH}	all Input	-	$0.8V_{DD}$			V
Input Low Voltage	V_{IL}			-	-	$0.2V_{DD}$	
I/O Port Source Current	I_{OH}	all Output	$V_{DD}=3.0V$ $V_{OH}=2.7V$	-	5	-	mA
			$V_{DD}=5.0V$ $V_{OH}=4.5V$	-	10	-	
I/O Port Sink Current	I_{OL}	all Output	$V_{DD}=3.0V$ $V_{OL}=0.3V$	-	15	-	
			$V_{DD}=5.0V$ $V_{OL}=0.5V$	-	30	-	
Power Supply Current	I_{DD}	Normal mode	$V_{DD}=4.2V$	-	8.8	-	µA
			$V_{DD}=3.0V$	-	3.7	-	
		Low Power mode	$V_{DD}=4.2V$	-	6.7	-	
			$V_{DD}=3.0V$	-	2.7	-	
Timeout Lead Time	T_{LT}		$V_{DD}=3V$	-	8	-	S
VDD slew rate after POR	V_{SR}		$V_{DD}=3V$	-0.1		0.1	V/S
LVR Voltage	V_{LVR}	TA=25°C		1.8	2.0	2.2	V



PACKAGE INFORMATION


Please note that the package information provided is for reference only. Since this information is frequently updated, users can contact Sales to consult the latest package information and stocks.

Ordering Information

Ordering number	Package
TK8811CS-100-A8	SOT23-6
TK8811CS-100-C1	DFN-6


Package Information

• SOT23-6 Package Dimension



SYMBOL	DIMENSION IN MM			DIMENSION IN INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	-	-	1.45	-	-	0.057
A1	0	0.08	0.15	0	0.003	0.006
A2	0.90	1.10	1.30	0.035	0.043	0.051
A3	0.60	0.65	0.70	0.024	0.026	0.028
c	0.12	0.16	0.19	0.005	0.006	0.007
D	2.82	2.92	3.02	0.111	0.115	0.119
E	2.70	2.90	3.10	0.106	0.114	0.122
E1	1.52	1.62	1.72	0.060	0.064	0.068
e	0.85	0.95	1.05	0.033	0.037	0.041
e1	1.80	1.90	2.00	0.071	0.075	0.079
L	0.35	0.48	0.60	0.014	0.019	0.024
θ	0°	4°	8°	0°	4°	8°
JEDEC	M0-178 (AB)					

△ * NOTES : ALL DIMENSIONS REFER TO JEDEC STANDARD MO-178 AB
DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.

DFN-6 Package Dimension


DIM SYMBOL	MIN.	NOM.	MAX.
A	0,70	0,75	0,80
	0,80	0,85	0,90
A1	0	0,02	0,05
A3	-	0,20 REF	-
b	0,25	0,30	0,35
D	2,00BSC		
E	2,00BSC		
D2	1,40	1,50	1,60
E2	0,70	0,80	0,90
e	0,65BSC		
L	0,30	0,35	0,40
K	0,25	-	-
aaa	0,15		
bbb	0,10		
ccc	0,10		
ddd	0,05		
eee	0,08		
fff	0,10		